

MAXIMUM CHARACTERISTICS

PAIRS PROTECTED:

1/2, 4/5, 3/6, 7/8

PINS PROTECTED:

ALL 8, L-L

TURN ON (@10mA):

±12Vdc TYPICAL, L-L

SERIES RESISTANCE:

<0.02Ω

TYPICAL CAPACITANCE:

55pF, L-L

MAX SURGE:

100A; 10/1000 USEC (BELLCORE 1089), L-L

HUMIDITY:

0 TO 100% CONDENSING

TEMPERATURE:


-40°C TO +85°C STORAGE/OPERATING

APPLICATION:

INDOOR, RJ45, UTP

TYPICAL WEIGHT:

0.2 lb.

| | | | | | | | |
|--------------------------------|-------------|-------------------------|---|----|--|------------------------|---------------------------|
| DRAWN BY R. SWART | | DATE 04/29/05 |  P.O. BOX 9000 MINDEN, NV 89423 TEL: 775.782.2511 FAX: 775.782.4476 | | UNLESS OTHERWISE STATED DIMENSIONS ARE IN INCHES TOLERANCES SURFACE FINISH = 63µin ANGLES = ±.5° .X = ±.05 .XX = ±.03 .XXX = ±.01 .XXXX = ±.005 DO NOT SCALE DRAWING | | |
| MECH ENG R. DUNNING | | DATE 05/16/05 | | | | | |
| ELEC ENG L. CHANG | | DATE 05/11/05 | PART NO / TITLE / DESCRIPTION NX1-05 CUSTOMER PRINT | | SCALE 1/1 | | |
| Q.A. DEPT L. JACQUES | | DATE 05/11/05 | | | | | |
| MKT DEPT S. DOTTER | | DATE 05/13/05 | ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE WRITTEN CONSENT OF POLYPHASER CORPORATION. | | PAGE 1 OF 1 | FILE TAG -C1 | CAGE CODE 61114 |
| REV | DESCRIPTION | DATE | ME | EE | MKT | QA | |