

MAXIMUM CHARACTERISTICS

PAIRS PROTECTED:
1/2, 4/5, 3/6, 7/8

PINS PROTECTED:
ALL 8, L-L

TURN ON (@10mA):
±70Vdc TYPICAL, L-L

SERIES RESISTANCE:
<0.02Ω

TYPICAL CAPACITANCE:
60pF, L-L


MAX SURGE:
100A; 10/1000 USEC (BELLCORE 1089), L-L

HUMIDITY:
0 TO 100% CONDENSING

TEMPERATURE:
-40°C TO +85°C STORAGE/OPERATING

APPLICATION:
INDOOR, RJ45, UTP

TYPICAL WEIGHT:
0.2 lb.

DRAWN BY R. SWART		DATE 04/29/05	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775.782.2511 FAX: 775.782.4476		UNLESS OTHERWISE STATED DIMENSIONS ARE IN INCHES TOLERANCES SURFACE FINISH = 63μin ANGLES = ±.5° .X = ±.05 .XX = ±.03 .XXX = ±.01 .XXXX = ±.005 DO NOT SCALE DRAWING		
MECH ENG R. DUNNING		DATE 05/16/05					
ELEC ENG L. CHANG		DATE 05/11/05	PART NO / TITLE / DESCRIPTION NX1-60 CUSTOMER PRINT		ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE WRITTEN CONSENT OF POLYPHASER CORPORATION.		
Q.A. DEPT L. JACQUES		DATE 05/11/05					
MKT DEPT S. DOTTER		DATE 05/13/05	SCALE 1/1	PAGE 1 OF 1	FILE TAG -C1	CAGE CODE 61114	
REV	DESCRIPTION	DATE	ME	EE	MKT	QA	