

MAXIMUM CHARACTERISTICS

PAIRS PROTECTED:

1/2, 4/5, 3/6, 7/8

PINS PROTECTED:

ALL 8, L-L & L-G

TURN ON (@10mA):

±12Vdc TYPICAL, L-L & L-G

SERIES RESISTANCE:

<0.02Ω

TYPICAL CAPACITANCE:

55pF, L-L & L-G

MAX SURGE:

100A; 10/1000 USEC (BELLCORE 1089), L-L & L-G

HUMIDITY:

0 TO 100% CONDENSING

TEMPERATURE:

-40°C TO +85°C STORAGE/OPERATING

APPLICATION:


INDOOR, RJ45, STP

TYPICAL WEIGHT:

0.2 lb.

NOTES:

- GROUND UNIT USING ATTACHED RING TERMINAL TO NEAREST POINT.

DRAWN BY R. SWART	DATE 04/29/05	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775.782.2511 FAX: 775.782.4476 NX2-05 CUSTOMER PRINT	UNLESS OTHERWISE STATED DIMENSIONS ARE IN INCHES TOLERANCES SURFACE FINISH = 63μin ANGLES = ±.5° .X = ±.05 .XX = ±.03 .XXX = ±.01 .XXXX = ±.005 DO NOT SCALE DRAWING			
MECH ENG R. DUNNING	DATE 05/16/05					
ELEC ENG L. CHANG	DATE 05/11/05					
Q.A. DEPT L. JACQUES	DATE 05/11/05					
MKT DEPT S. DOTTER	DATE 05/13/05					
REV	DESCRIPTION	DATE	SCALE 1/1	PAGE 1 OF 1	FILE TAG -C1	CAGE CODE 61114