


ALL DESIGN, OPERATIVE AND PROCESS DATA PERTAINING TO THE ARTICLE SHOWN ON THIS SHEET IS THE PROPERTY OF POLYPHASER CORPORATION. THE INFORMATION IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF POLYPHASER CORPORATION.

REVISIONS

REV	LTR	DATE	ENG	MKTG	Q.A.
-----	-----	------	-----	------	------




MAXIMUM CHARACTERISTICS

APPLICATION:
BULKHEAD MOUNT
WEATHERPROOF WHEN INSTALLED
SURGE:
30kA IEC 61000-4-5 8/20 μ s WAVEFORM
FREQUENCY RANGE:
800MHz TO 2.3GHz @ 1.1:1 VSWR TYPICAL
700MHz TO 2.5GHz @ 1.2:1 VSWR
INSERTION LOSS:
 ≤ 0.1 dB
CONTINUOUS POWER:
500W @ 85°C
750W @ 40°C
1kW @ 20°C
LET THROUGH VOLTAGE:
 $\leq \pm 3$ VOLTS FOR 3kA @ 8/20 μ s WAVEFORM
THROUGHPUT ENERGY:
 ≤ 0.5 μ J FOR 3kA @ 8/20 μ s WAVEFORM
TEMPERATURE:
-40°C TO +85°C STORAGE/OPERATING
VIBRATION:
1G AT 5Hz TO 100Hz
ENVIRONMENTAL:
MEETS IEC 60529 IP65.
MEETS BELLCORE #TA-NWT-000487
PROCEDURE 4.11, WIND DRIVEN (120MPH)
RAIN INTRUSION TEST.

CUSTOMER APPROVAL: _____ DATE: _____

ALL DIMENSIONS SHOWN ABOVE ARE FOR REFERENCE ONLY.

DRAFTER S. HALL	DATE 07/21/05	 P.O. BOX 9000 MINDEN, NV 89423 TEL: 775-782-2511 FAX: 775-782-4476 DWG NO/PART NO/DESCRIPTION DSXL-DN-ME CUSTOMER PRINT			
MECH ENGINEER R. DUNNING	DATE 07/25/05				
ELEC ENGINEER J. JONES	DATE 07/25/05				
MARKETING S. DOTTER	DATE 07/25/05				
QUALITY DEPT L. JACQUES	DATE 07/25/05	CAGE CODE 61114	FILE NAME -C1	SCALE 1/1	SHEET 1 OF 1